

ECCENTRIC / CONCENTRIC


DIMENSIONS (mm)													
SIZE	A	B	C	E	F	H (in.)	I	J	S	T	VID (in.)	VD (in.)	W (in.)
VWAC-1	M6x1.0	6.0	17.1	-	2.1	7/16	2.5	5.97	6.1	8.9	0.625	0.781	0.310
VWAC-2	M10x1.5	8.2	27.5	-	2.6	9/16	5.5	9.97	9.9	15.0	1.000	1.219	0.437
VWAC-3	M12x1.75	11.4	33.5	-	3.5	3/4	6.0	11.97	12.1	17.9	1.500	1.813	0.625
VWAC-4	M16x2.0	12.6	43.2	-	3.1	7/8	8.0	15.97	16.0	24.1	2.750	2.375	0.750
VWAE-1	M6x1.0	6.0	17.1	0.61	2.1	7/16	2.5	5.97	6.1	8.9	0.625	0.781	0.310
VWAE-2	M10x1.5	8.2	27.5	0.97	2.6	9/16	5.5	9.97	9.9	15.0	1.000	1.219	0.437
VWAE-3	M12x1.75	11.4	33.5	1.50	3.5	3/4	6.0	11.97	12.1	17.9	1.500	1.813	0.625
VWAE-4	M16x2.0	12.6	43.2	1.50	3.1	7/8	8.0	15.97	16.0	24.1	2.750	2.375	0.750

SPECIFICATIONS & OPTIONS

- Studded guide rollers are made from standard Modern Linear "VW" guide rollers and a swaged stainless steel mounting stud.
- They are available in concentric (non-adjustable) versions, (VWIC) and eccentric (adjustable) versions (VWIE).
- All studded rollers include a hex socket for easy mounting.
- They can be ordered with 52100 steel "VW" rollers as well as stainless steel, sealed rollers, designated with - SSX suffix.
- Stainless steel nut and washer available if needed.
- All dimensions are industry standard ($\pm .005$ inches), unless otherwise specified.

MATERIALS

ROLLER	STEEL	STAINLESS
Outer	52100	440 SS
Inner	52100	440 SS
Balls	52100	440 SS
Retainer	NYLON66	NYLON66
Grease	NLGI #2	NLGI #2
Stud	303 SS	303 SS



GUIDE ROLLER CAPACITY (lbs.)

SIZE	LR	LA	MAX RPM	WEIGHT
1	134	57	2400	0.04
2	322	140	1500	0.13
3	691	382	1000	0.43
4	1058	899	750	0.90

NOMENCLATURE

STUDED GUIDE ROLLER VWAC - 2 - SS - X
 Studded Guide Roller Size Sealed Stainless Steel